

## Product Highlights

### Flexible operation and handling

- ★Ultra stable design greatly improves safety factor. Featuring compact body, and wide operating area
- ★Standard forklift hole, high equipment transportation turnover efficiency, and convenient transportation

### Reduce maintenance costs

- ★High universality of components and no pressure on spare parts
- ★Drawer style door design for more convenient maintenance and upkeep
- ★Self diagnosis of faults, displaying fault information for rapid troubleshooting

### More reliable performance

- ★Multiple protection for lifting circuit, safe and reliable
- ★Anti collision strip protection, more effective in preventing scratches and collisions



### XE-A Series Standard Features

- Auxiliary, can operate by one person for drive
- Hydraulic line rupture protection device
- Screw support levelling device
- Emergency stop button
- Emergency lower down
- Rain-proof control box
- Automatically battery charger

### XE-A Options Features

- Extended platform (6-12m)

### XE-M Series Standard Features

- |  |                                |
|--|--------------------------------|
| Emergency Lower down                     | Screw support levelling device |
| Rain-proof control box                   | Emergency stop button          |
| Hydraulic line rupture protection device |                                |

### XE-M Options Features

- Power: AC220V(6-11), DC24/48V, manual hydraulic power
- Extended platform
- Rubber solid tires



**XE-A/M SERIES**  
**XE-A80H/A110H/A140H**  
**MOBILE ELECTRIC SCISSOR LIFT**

<b>Model</b>		<b>XE-A80H</b>
<b>Dimension</b>	<b>Metric</b>	<b>Imperial</b>
Max. Working Height m	8m	26ft 3in
Max. Platform Height m	6m	19ft 8in
Lifting Capacity KG	1000kg	2205lb
Platform Size mm	1800mm*1000mm	71in*39in
Stowed Size m	1.85m*1.24m*1.11m	6ft1in*4ft1in*3ft8in
Rising Time	80s	80s
Traction Speed s	0-16.8s	0-16.8s
Power Source	DC-24V	DC-24V
Lifting Motor Power kw	3kw	3kw
Driving Motor Power kw	0.75kw	0.75kw
Weight kg	960kg	2116 lb
<b>Model</b>		<b>XE-A110H</b>
<b>Dimension</b>	<b>Metric</b>	<b>Imperial</b>
Max. Working Height m	11m	36ft 1in
Max. Platform Height m	9m	29ft 6in
Lifting Capacity KG	1000kg	2205lb
Platform Size mm	1800mm*1250mm	71in*49in
Stowed Size m	1.85m*1.49m*1.65m	6ft1in*4ft11in*5ft5in
Rising Time	108s	108s
Traction Speed s	0-16.8s	0-16.8s
Power Source	DC-24V	DC-24V
Lifting Motor Power kw	3kw	3kw
Driving Motor Power kw	1.2kw	1.2kw
Weight kg	1850kg	4079 lb
<b>Model</b>		<b>XE-A140H</b>
<b>Dimension</b>	<b>Metric</b>	<b>Imperial</b>
Max. Working Height m	14m	45ft 11in
Max. Platform Height m	12m	39ft 4in
Lifting Capacity KG	1000kg	2205lb
Platform Size mm	2450mm*1350mm	96in*53in
Stowed Size m	2.5m*1.59m*1.85m	8ft2in*5ft3in*6ft1in
Rising Time	128s	128s
Traction Speed s	0-16.8s	0-16.8s
Power Source	DC-24V	DC-24V
Lifting Motor Power kw	2.2kw*2kw	2.2kw*2kw
Driving Motor Power kw	1.2kw	1.2kw
Weight kg	2260kg	4982 lb

The images in this manual are for illustration only, and all copyrights belong to our company. Due to continuous technological updates, product parameters may change without prior notice.



Mentall XE-A110H

Mentall XE-A110H