

Product Highlights

Flexible operation and handling

- ★Ultra stable design greatly improves safety factor. Featuring compact body, and wide operating area
- ★Standard forklift hole, high equipment transportation turnover efficiency, and convenient transportation

Reduce maintenance costs

- ★High universality of components and no pressure on spare parts
- ★Drawer style door design for more convenient maintenance and upkeep
- ★Self diagnosis of faults, displaying fault information for rapid troubleshooting

More reliable performance

- ★Multiple protection for lifting circuit, safe and reliable
- ★Anti collision strip protection, more effective in preventing scratches and collisions



XE-A Series Standard Features

- Auxiliary, can operate by one person for drive
- Hydraulic line rupture protection device
- Screw support levelling device
- Emergency stop button
- Emergency lower down
- Rain-proof control box
- Automatically battery charger

XE-A Options Features

- Extended platform (6-12m)

XE-M Series Standard Features

- | | |
|--|--------------------------------|
| Emergency Lower down | Screw support levelling device |
| Rain-proof control box | Emergency stop button |
| Hydraulic line rupture protection device | |

XE-M Options Features

- Power: AC220V(6-11), DC24/48V, manual hydraulic power
- Extended platform
- Rubber solid tires



Model		XE-M50S		XE-M80S
Dimension	Metric	Imperial	Metric	Imperial
Max. Working Height m	5m	16ft 5in	8m	26ft 3in
Max. Platform Height m	3m	9ft 10in	6m	19ft 8in
Lifting Capacity KG	450kg	992lb	450kg	992lb
Platform Size mm	1300mm*700mm	51in*28in	1850mm*880mm	73in*35in
Stowed Size m	1.35m*0.94m*0.8m	4ft5in*3ft1in*2ft7in	2.16m*1.3m*1.65m	7ft1in*4ft3in*5ft5in
Rising Time s	30s	30s	54s	54s
Motor Power kw	0.75kw	0.75kw	1.1kw	1.1kw
Power Source	AC220V/380V	AC220V/380V	AC220V/380V	AC220V/380V
Weight kg	450kg	992 lb	650kg	1433 lb
Tire Size	Φ250 rubber solid tires	Φ250 rubber solid tires	Φ250 rubber solid tires	Φ250 rubber solid tires
Model		XE-M95S		XE-M110S
Dimension	Metric	Imperial	Metric	Imperial
Max. Working Height m	9.45m	31ft 0in	11m	36ft 1in
Max. Platform Height m	7.45m	24ft 5in	9m	29ft 6in
Lifting Capacity KG	450kg	992lb	450kg	992lb
Platform Size mm	1800mm*1000mm	71in*39in	1800mm*1000mm	71in*39in
Stowed Size m	2.16m*1.3m*1.8m	7ft1in*4ft3in*5ft11in	2.16m*1.3m*1.8m	7ft1in*4ft3in*5ft11in
Rising Time s	72s	72s	80s	80s
Motor Power kw	1.5kw	1.5kw	1.5kw	1.5kw
Power Source	AC220V/380V	AC220V/380V	AC220V/380V	AC220V/380V
Weight kg	1100kg	2425 lb	1260kg	2778 lb
Tire Size	Φ400-8 rubber solid tires	Φ400-8 rubber solid tires	Φ400-8 rubber solid tires	Φ400-8 rubber solid tires
Model		XE-M130S		XE-M140S
Dimension	Metric	Imperial	Metric	Imperial
Max. Working Height m	13m	42ft 8in	14m	45ft 11in
Max. Platform Height m	11m	36ft 1in	12m	39ft 4in
Lifting Capacity KG	450kg	992lb	450kg	992lb
Platform Size mm	2100mm*1150mm	83in*45in	2450mm*1350mm	96in*53in
Stowed Size m	2.4m*1.4m*1.8m	7ft10in*4ft7in*5ft11in	2.68m*1.6m*1.9m	8ft10in*5ft3in*6ft3in
Rising Time s	88s	88s	90s	90s
Motor Power kw	2.2kw	2.2kw	3kw	3kw
Power Source	AC220V/380V	AC220V/380V	AC220V/380V	AC220V/380V
Weight kg	1380kg	3042 lb	1850kg	4079 lb
Tire Size	Φ500-8 rubber solid tires	Φ500-8 rubber solid tires	Φ500-8 rubber solid tires	Φ500-8 rubber solid tires
Model		XE-M160S		XE-M180S
Dimension	Metric	Imperial	Metric	Imperial
Max. Working Height m	16m	52ft 6in	18m	59ft 1in
Max. Platform Height m	14m	45ft 11in	16m	52ft 6in
Lifting Capacity KG	450kg	992lb	300kg	661lb
Platform Size mm	2450mm*1350mm	96in*53in	2700mm*1500mm	106in*59in
Stowed Size m	2.7m*1.6m*2.1m	8ft10in*5ft3in*6ft11in	3.1m*1.75m*2.1m	10ft2in*5ft9in*6ft11in
Rising Time s	120s	120s	130s	130s
Motor Power kw	3kw	3kw	3kw	3kw
Power Source	AC220V/380V	AC220V/380V	AC220V/380V	AC220V/380V
Weight kg	2150kg	4740 lb	2680kg	5908 lb
Tire Size	Φ500-8 rubber solid tires	Φ500-8 rubber solid tires	Φ500-8 rubber solid tires	Φ500-8 rubber solid tires

The images in this manual are for illustration only, and all copyrights belong to our company. Due to continuous technological updates, product parameters may change without prior notice.

